

REV.	ECN NO.	DATE
A	RELEASED	09/25/00
D	Add Part Number	09/01/03
E	Reverse Part No.	01/14/05

NOTES:

\* Material

Body:FR-Nylon With 30% Glass Fiber  
Flammability UL 94V-0 Rated.



Color: Black.

Contact: Phosphor Bronze.

Contact: Tin Plated Over Nickel or Copper.


\* Specification

Application For 3V Lithium Battery.  
Dielectric Withstanding Voltage: 500 VDC  
Operation Temperature: -55°C To +105°C  
Durability: 50 Cycles Min.  
Contact Resistance: 30 Milliohms.



VIEW A  
9:1

P.C. BOARD LAYOUT



Units	mm	Scale	Drawing By	Date	IF TECHNOLOGY, INC.	Sheet	Title	Strsight Battery Housing(No Post)	REV
Tolerance Unless			Jason	01/14/05	TEL: 886-3-5511680 FAX 886-3-5511605	01/14/05	1 of 1		
Otherwise Specified			Sharon	01/14/05					
.X	$\pm 0.38$		Approval By	Date					
.XX	$\pm 0.25$		Amy	01/14/05					
.XXX	$\pm 0.20$								
Angle	$\pm 3^\circ$								