




REV.	ECN NO.	DATE
A	RELEASED	06/06/14



NOTES:

MATERIAL:  
HOUSING: PBT+25%G/F, UL94V-0, COLOR: **BLACK**.  
CONTACT: BRASS.

FINISH:  
CONTACT: TIN PLATED ALL OVER.  
50u" MIN. NICKEL UNDERPLATED ALL OVER.

SPECIFICATION:  
CURRENT RATING: 1 AMP. MAX.  
DIELECTRIC WITHSTAND VOLTAGE: 600V AC R.M.S. FOR 1 MINUTE.  
INSULATION RESISTANCE: 1,000MΩ MIN. AT 500V DC.  
OPERATING TEMPERATURE: -55°C TO +105°C.



Units	mm	Scale	1:1	Drawing By	Date	IF TECHNOLOGY, INC.					
Tolerance Unless Otherwise Specified				JIMMY	06/06/14	TEL: 886-3-5511680 FAX: 886-3-5511605					
				Reviewed By	Date						
.X    ± 0.38				SHARON	06/06/14						
.XX   ± 0.25				Approval By	Date						
.XXX   ± 0.20				JASON	06/06/14						
Angle   ± 3°											
						CR2032 BATTERY HOLDER, DIP					
				Title							
				Sheet 1 of 1							
				Third Angle Projection							
				Part No.		HBAT-002-RFD-20		REV		A	